



CC

Motor 电机类型	Shaded Pole Motor 罩极异步电动机
Motor Type 电机型号	Y216-25
Voltage 额定电压 (V)	220
Frequency 频率 (Hz)	50/60
Input Power 额定输入功率 (W)	≤60
Current 额定电流 (A)	≤0.4
Speed 额定转速 (rpm)	1300/1550±150
Load Starting Voltage 负载启动电压 (V)	≤176
Fan Blades 负载 (风叶)	ø250/28°
Rotation 转向	CCW
Airflow Direction 风向	Sucking or Blowing 吸风或吹风
Motor Protection 电机保护	Impedance protected 阻抗保护
Insulation Class 绝缘等级	B
Temperature Rise 运行温升	≤70K
Protection Class 防护等级	IP 42
Operating Type 工作制	S1
Mounting Type 安装角度	Horizontal or Vertical 水平或垂直
Ambient Temperature 适合环境温度	-30℃——+60℃
Electrical Connection 电源线	3*0.5mm ² lead wire
HI-POT Test 耐压	1800V/1S 1mA
bearing 轴承类型	Sleeve bearing 含油轴承
Endplay 轴向窜动	0.5-2mm
Approvals 认证	CE
Weight Per Unit 重量	1.4kg
Packing 包装	46*34*15.5cm 12pcs/CIN

[illegible]